

Product data FASSON TYRE PLUSImprint / **AFU475**

EAN Code :

8712739257373

Issue date : 30-Oct-
2007**FaceStock**

A white, woodfree, printing paper with semi gloss appearance laminated to a flexible aluminium barrier foil.

Basis Weight 82g/m² ISO 536

Caliper 0.060mm ISO 534

Adhesive

A special purpose permanent, rubber based adhesive.

Liner

BG50 white, a supercalendered glassine paper.

Basis Weight 78g/m² ISO 536

Caliper 0.068mm ISO 534

Transparency 42% DIN 53147

Laminate

Total Caliper 0.178mm +/- 10%

PERFORMANCE DATA

Initial Tack 1760N/m FTM 9

Peel Adhes. 90° 960N/m FTM 2

Min. appl. temp. -0 °C

Service temp. -20 °C --> +70 °C

Adhesive performance

This highly aggressive rubber based adhesive is specially designed for use on difficult and rough substrates such as tires.

Applications and use

FASSON Tyre Plus is specially designed to meet the performance requirements of automotive tyre labelling. The special composition provides a superb anchorage of the label to the compound curved and extremely irregular surface of tyres, neglecting the negative influences of surface contaminants such as mould release agents or components migrating from the rubber.

The aluminum barrier foil prevents migration of components through the facestock thus avoiding the label from getting stained.

Conversion / Printing

Extensive testing has proven satisfactory conversion by both rotary and flatbed, although experience has learned that flatbed is the preferred technology. The heavy adhesive coatweight does not allow high conversion speeds, special care is required with regard to die-cutting and matrix stripping. Sharp, high quality dies are required to assure smooth matrix stripping and to avoid problems in eventual automatic or semi-automatic label dispensing. Heat, used for ink drying, may have a negative effect on conversion or dispensing and should be avoided. If necessary a temperature level of 50 °C should not be exceeded. Printing can be done in all applicable label printing technologies.

Important Note : To avoid adhesive bleed label roll should not be wound tight and not be exposed to elevated temperature during storage : Gumpattern is strongly recommended.

Shelf life

One year stored at 22 °C +/- 2 °C and 50 +/- 5% RH.

N.B. : All data to be considered as typical values.



Avery Dennison Roll Materials Europe
Lammenschansweg 140, P.O. Box 28
NL - 2300 AA Leiden - The Netherlands
Tel +31 71 5794100 - Fax +31 71
5794180
<http://www.europe.fasson.com>

Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge or AVERY DENNISON may issue credit in such amount as it deems reasonable however, in no event shall AVERY DENNISON be responsible for claims beyond the replacement value of the defective product or in any way liable or responsible for consequential or incidental damages.

NO EXPRESS WARRANTIES AND NO IMPLIED WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON.

No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.
